

## Feature Summary

- Lossless Packet Capture
- Gigamon, Arista Timestamp
- Packet Merging
- Packet Parsing
- Tunneling Protocol Processing
- Packet Slicing
- Packet Steering
- DMA (Direct Memory Access)
- Multi-core DMA
- Timestamp 10 nS
- RMON1 (RFC 2819) Statistics
- Onboard Sensors



## ANIC-2KL

### Dual GigE PCI Express Packet Capture Adapter

The ANIC-2KL is a low-cost, state of the art dual port 1 GigE PCI Express adapter designed for Network Monitoring applications. The product is built around Accolade's Advanced Packet Processor (APP) featuring a scalable pipelined architecture, implemented in an FPGA. The APP platform allows for seamless integration of packet processing algorithms.

The ANIC-2KL is designed to offload the Host CPU in applications that demand full 2 Gbps Packet Capture at all Packet Sizes. The ANIC performs precise Time Stamping, Packet Filtering, Packet Slicing and Classification. Presenting data in a programmable number of DMA rings, the ANIC-2KL performs load balancing to optimize Multi-Core CPU Resources.

### Timing Sub-System

The ANIC-2KL is designed to interface and synchronize to precise timing input from GPS and CDMA timing sources via a RS232, RS422 or TTL input/output for precise 1 pps. The timing sub-system in the ANIC-2KL features a Temperature Controlled Crystal Oscillator (TCXO) as a stable high precision clock source. IEEE-1588 timing distribution is supported via a dedicated 10/100 Ethernet port. The ANIC-2KL supports popular timing sources such as Trimble and Endrun. A packet time stamp to a resolution of 8ns is applied to all captured packets.

### Software Support

The ANIC-2KL is available complete with a software development guide that includes Diagnostics Utilities, Linux and FreeBSD Drivers, and a comprehensive API supporting all embedded services including Filtering, Classification, Packet Steering, Timing Sub-system configuration, and IEEE1588 Support.

## Applications

- Passive and Inline Network Monitoring
- Network Latency Measurement
- Packet Generator / Playback
- Network Forensics
- Intrusion Detection
- Load Balancing

## ANIC-2KL Hardware Specifications

<b>PCI Interface</b>	4 lanes 2.5MHz PCI Express
<b>Ethernet Compliance</b>	802.3 IEEE Dual SFP Modules
<b>Time Stamping</b>	Resolution to 8 nS
<b>Timing Interfaces</b>	RS232/RS422 for External 1 PPS Integrated IEEE-1588 V2 Receiver
<b>Packet Memory</b>	256 MB
<b>Flash Memory</b>	4 MB
<b>Compliance</b>	EMI per FCC Part 15/EN 55022/VCCI/AS/NZS Immunity per EN 55024
<b>Power</b>	Less than 12 Watts
<b>Operating Temperature</b>	0 to 50 deg C
<b>Operating Humidity</b>	0 to 95% non-condensing
<b>Card Dimensions</b>	PCI Express Full Height, Half Length